

DYNAMIKSEILE | TECHNISCHE DATEN

Linie	Name	Modellnummer	Seiltyp	Technologien										
				3D-LapCoiling	Pro Dry	Eco Dry	Thermo Shield	Sports Braid	Duotec	colorTEC	Linktec	Sync tec	Cut Protect	
Protect Line	Swift Protect Pro Dry 8,9 mm	71289	① ½ ②											
	Eagle Lite Protect Pro Dry 9,5 mm	71343	①											
	Starling Protect Pro Dry 8,2 mm	71318	½ ②											
Pro Line	Siskin Eco Dry 8,6 mm	71367	① ½ ②											
	Canary Pro Dry 8,8 mm	71368	① ½ ②											
	Swift 48 Eco Dry 8,9 mm	71358	① ½ ②											
	Swift 48 2R Eco Dry 8,9 mm	71357	① ½ ②											
	Hummingbird Eco Dry 9,2 mm	71342	①											
	Tommy Caldwell Eco Dry DT 9,6 mm	71317	①											
	Eagle Lite Eco Dry 9,5 mm	71341	①											
	Tommy Caldwell Eco Dry 9,6 mm	71334	①											
	Heron Eco Dry 9,8 mm	71335	①											
	Skimmer Eco Dry 7,1 mm	71292	½ ②											
	Apus Eco Dry 7,9 mm	71360	½ ②											
	Starling Eco Dry 8,2 mm	71359	½ ②											
	Sports	Kinglet 9,2 mm	71291	①										
		Eagle Lite 9,5 mm	71239	①										
Parrot 2R 9,6 mm		71363	①											
Neo 100 3R 9,6 MM		71362	①											
Birdlime 1R 9,8 mm		71366	①											
Boa 9,8 mm		71079	①											
Boa Gym 9,8 mm		71281	①											
Python 10,0 mm		71080	①											
Tower Lite 10,0 mm		71220	①											
	Tower 10,5 mm	71057	①											

DYNAMIKSEILE | TECHNISCHE DATEN

Modellnummer	Eis / Mixed Klettern	Alpinklettern	Alpines Sportklettern	Big Wall	Sportklettern	Projektieren	Indoor	Toprope	Durchmesser (mm)	Gewicht (g/m)	Mantelanteil (%)	Sturzzahl	Fangstoß	Dynamische Dehnung (%)	Statische Dehnung (%)	Mantelverschleiß	Schnittwert*
	Anwendungsgebiete								Produkteigenschaften								
71289	✓	✓	✓		✓				8,6	51	47	5 / 24 / 30	8,4 / 6,4 / 10,6	32 / 31 / 28	7,4 / 7,1 / 5,6	0	14
71343	✓		✓	✓	✓	✓	✓	•	9,5	57	38	6	8,7	32,0	4,7	0	28,5
71318	✓	✓	✓						8,2	44	42	7 / 20	7,0 / 11,8	28 / 24	8,8 / 5,1	0	23
71367	✓	✓	✓		✓				8,6	48	38	5 / 8 / ≥25	8,5 / 6,5 / 10,7	35 / 33 / 30	4,9 / 4,6 / 4	0	
71368	✓	✓	✓		✓				8,8	52	47	5 / 24 / 30	8,4 / 6,4 / 10,6	32 / 31 / 28	7,4 / 7,1 / 5,6	0	14
71358	✓	✓	✓		✓		•		8,9	53	41	6 / 20 / 22	8,7 / 6,5 / 10,8	34 / 28 / 28	6,2 / 6,2 / 5,0	0	15
71357	✓	✓	✓		✓		•		8,9	53	41	6 / 20 / 22	8,7 / 6,5 / 10,8	34 / 28 / 28	6,2 / 6,2 / 5,0	0	15
71342	•	✓	✓	✓	✓	•			9,2	57	44	8	8,8	31,0	6,0	0	15
71317	•	✓	✓	✓	✓	•			9,3	57	61	7	9	34	7,40	0	22
71341	✓		✓	•	✓	✓	✓	•	9,5	60	36	10	9,3	31,0	7,5	0	20
71334		•	✓	✓	✓	✓	✓	•	9,6	62	40	8	9,1	31,0	7,4	0	20
71335	•		✓	•	✓	✓	✓	•	9,8	63	39	10	9,3	34,0	7,4	0	28
71292	✓	✓	✓						7,1	36	40	5 / 18	6,1 / 10,0	32 / 29	9,0 / 5,2	0	11
71360	✓	✓	✓						7,9	43	33	9 / 30	6,7 / 10,3	30 / 27	7,7 / 4,8	0	14
71359	✓	✓	✓						8,2	45	42	11 / >25	6,2 / 9,8	30 / 27	8,7 / 4,9	0	16
71291				•	✓	✓	✓	✓	9,2	56	37	7	8,8	31,0	6,0	0	16
71239				•	✓	✓	✓	•	9,5	62	36	9	9,0	29,0	7,1	0	20
71363			•		✓	✓	•	•	9,6	57	41	7	7,9	38	7,8	0	
71362					✓	✓	✓	•	9,6	59	49	7	8,4	38	7,8	0	
71366					✓	✓	✓	•	9,8	60	41	6	8,5	35	5,2	0	
71079					✓	✓	✓	•	9,8	62	40	7	8,8	32,0	9,3	0	19
71281					•	✓	✓		9,8	68	41	7	8,8	32,0	5,5	0	32
71080				•	✓	✓	✓	•	10,0	64	38	8	8,9	32,0	10,0	0	21
71220						✓	✓	✓	10,0	66	41	9	8,7	34,0	8,0	0	33
71057						✓	✓	✓	10,5	69	39	9	8,4	34,0	9,2	0	33



* Schnittwert bei einer Vorlast von 100 kg.
Weitere Informationen findest du in unserer EDELRID Knowledge Base.