

NAME <i>NAME</i>	MODELLNUMMER <i>MODEL NUMBER</i>	DURCHMESSER <i>DIAMETER</i>	SEILTYP <i>ROPE TYPE</i>	METERGEWICHT <i>WEIGHT/METER</i>	MINDESTBRUCH- KRAFT <i>MIN. BREAKING STRENGTH</i>	MINDESTBRUCH- KRAFT ACHTER- KNOTEN <i>MIN. BREAKING STRENGTH IN FIGURE OF 8 KNOT</i>	STATISCHE DEH- NUNG <i>STATIC ELONGATION</i>	MANTEL- VERSCHIEBUNG <i>SHEATH SLIPPAGE</i>	MANTEL- ANTEIL <i>SHEATH PROPORTION</i>	SCHRUMPUNG H ₂ O <i>SHRINKAGE H₂O</i>	KNOTBARKEIT <i>KNOTABILITY</i>
Interstatic Protect	83238	11,0 mm	A	77 g/m	35 kN	20 kN	2,0 %	0mm	44 %	2 %	1,1
Static Low Stretch	83211	10,5 mm	A	74 g/m	30 kN	19 kN	1,9 %	0mm	42 %	2 %	1
Static Low Stretch	83213	11,0 mm	A	82 g/m	34 kN	20 kN	1,8 %	0mm	44 %	2 %	0,9
Performance Static	83202	9,0 mm	B	53 g/m	23 kN	12 kN	4,9 %	0mm	40 %	3 %	0,9
Performance Static	83204	10,0 mm	A	66 g/m	25 kN	16 kN	3,7 %	0mm	37 %	4 %	0,9
Performance Static	83205	10,5 mm	A	72 g/m	28 kN	18 kN	3,7 %	0mm	36 %	4 %	1
Performance Static	83206	11,0 mm	A	79 g/m	34 kN	22 kN	3,4 %	0mm	41 %	4 %	1
Performance Static	83208	12,0 mm	A	93 g/m	38 kN	25 kN	3,0 %	0mm	38 %	4 %	1
Prostatic SyncTec	83236	10,5 mm	A	79 g/m	36 kN	20 kN	2,8 %	0mm	40 %	2 %	1
Prostatic SyncTec	83237	11,0 mm	A	85 g/m	38 kN	22 kN	2,5 %	0mm	37 %	2 %	1
Powerstatic	83225	11,0 mm	A	81 g/m	29 kN	17 kN	4,3 %	0mm	39 %	0 %	0,7
Pintail Lite	71348	9,0 mm	B	56 g/m	25 kN	17 kN	3,0 %	0mm	44 %	0 %	0,8
Pintail	71349	10,0 mm	A	70 g/m	30 kN	17 kN	2,9 %	0mm	40 %	0 %	0,9