

NAME NAME	MODELLNUMMER 	DURCHMESSER DIAMETER	SEILTYP ROPE TYPE	METERGEWICHT WEIGHT/METER	MINDESTBRUCH-KRAFT MIN. BREAKING STRENGTH	MINDESTBRUCH-KRAFT ACHTER-KNOTEN MIN. BREAKING STRENGTH IN FIGURE DFBKNOT	STATISCHE DEH-NUNG STATIC ELONGATION	MANTEL-VERSCHIEBUNG SHEATH SL/PPAGE	MANTEL-ANTEIL SHEATH PROPORTION	SCHRUMPUNG H ₂ O SHRINKAGE H ₂ O	KNOTBARKEIT KNOTABILITY
Interstatic Protect	83238	11,0mm	A	77g/m	35 kN	20kN	2,0%	0mm	44%	2%	11
Static Low Stretch	83211	10,5mm	A	74 g/m	30 kN	19 kN	1,9 %	0mm	42 %	2%	1
Static Low Stretch	83213	11,0mm	A	82g/m	34 kN	20kN	1,8%	0mm	44%	2%	0,9
Performance Static	83202	9,0mm	B	53 g/m	23 kN	12 kN	4,9 %	0mm	40%	3%	0,9
Performance Static	83204	10,0mm	A	66g/m	25 kN	16 kN	3,7%	0mm	37%	● ●	0,9
Performance Static	83205	10,5mm	A	72 g/m	28 kN	18 kN	3,7%	0mm	36%	● ●	1
Performance Static	83206	11,0mm	A	79 g/m	34 kN	22 kN	3,4%	0mm	41%	● ●	1
Performance Static	83208	12,0mm	A	93 g/m	38 kN	25 kN	3,0%	0mm	38%	● ●	1
Prostatic SyncTec	83236	10,5mm	A	79 g/m	36 kN	20kN	2,8%	0mm	40%	2%	1
Prostatic SyncTec	83237	11,0mm	A	85g/m	38 kN	22 kN	2,5%	0mm	37%	2%	1
Powerstatic	83225	11,0mm	A	81 g/m	29 kN	17 kN	4,3%	0mm	39 %	0%	0,7
Pintail Lite	71348	9,0mm	B	58g/m	25 kN	13 kN	3,5%	0mm	44%	1,5%	0,8
Pintail	71349	10,0mm	A	70g/m	30 kN	17 kN	2,9%	0mm	40%	0%	0,9